



Nilfisk-Advance America

CFM 125 VACUUM



CFM 125 Vacuum

Maintain a healthy, dust-free environment and protect the quality of your work with the CFM 125 industrial vacuum cleaner. The CFM 125 is ideal for use with surface preparation tools and equipment in the concrete, woodworking and general construction industries.

Features and Benefits:

- Durable, lightweight plastic design
- Powered by two 800 watt bypass motors
- Oversized main filter ensures minimal maintenance, reducing down time.
- External filter shaker handle maintains the vacuum's maximum suction power and filtration performance
- Equipped with a paper bag filter for fine dust collection
- Optional upstream HEPA filter for safe containment of collected debris. HEPA filter exceeds standards of 99.97% efficiency, down to and including 0.3 microns
- Ergonomic container release for easy emptying
- Large fixed rear wheels and locking swivel casters for improved maneuverability
- Low maintenance
- Ideal for use with a wide variety of walk-behind and hand-held tools



Nilfisk-Advance America

CFM 125 Vacuum

Specifications for the CFM 125 Vacuum

Data	Units	CFM 125
No. of phases		1
Voltage @ 60 Hz	volts	115
Amperage, max.	amps	14
Rated power	watts	1600
Vacuum, max.	inches H ₂ O	78.7
Airflow, max.	cfm	184
Sound level	d(B)A	78
Protection class	IP	43
Insulation class	class	F
Main filter area	sq. ft.	16.15
HEPA filter area*	sq. ft.	32.3
Inlet diameter	in/mm	2/50
Collection capacity	gallons/liters	10/40
Dimensions (lxwxh)	inches	25.3x22.4x39.4
Cord length	feet	30
Weight	lbs	75

* Actual HEPA exhaust filter efficiency: 99.995% @ 0.18 microns (MPPS method)



Visit us online at www.pa.nilfisk-advance.com

Nilfisk-Advance America, Inc.
300 Technology Drive
Malvern, PA 19355-1315

1-800-NILFISK
Fax: (610) 647-6427